

Automatic Weather Station by INGEN Technologies



Table of Content

About Ingen

AWS Network & Capability Validation
IMD Certification

Why us?

AWS Data Flow Diagram

AWS Application

- I) Weather Forecasting & Weather Data Services
- ii) Sensor Management System
- iii) Risk Management
- iv) Agri Advisory

Technical Specifications of AWS Sensors

Integrated Data logger
Communication Unit (IDCU for AWS iDAS101)
Power Supply

Application Software

Clientele

Click To Go
Directly On Page

03

04

05

06

07

08

09

10

11


About Us

Wholly-owned subsidiary of WRMS

Ingen Technologies Private Limited, founded in the year 2008 as a subsidiary of Weather Risk Management Services Private Limited, is a leading Weather Service provider in India, with a supply of more than 15,000 Automatic Weather Stations (AWSs) & Automatic Rain Gauges (ARGs) across the globe and more than 10,000 installations PAN India.

Ingen leverages indigenously manufactured advanced technology, and its strong in-house team of meteorologists, remote sensing experts, and IoT specialists, to provide weather data & forecasting services to various corporations and government organizations in insurance, energy, and agriculture sectors.

Global Footprint



AWS Network

+10,000 AWS across India



In collaboration with various State Government



IMD Certification

ISO 90012015 INGEN



PRESSURE SENSOR



SILICON PYRANOMETER



TEMPERATURE RELATIVE HUMIDITY SENSOR



TIPPING BUCKET RAIN GAUGE



ULTRASONIC WIND SPEED & DIRECTION SENSOR





Why Us?

1. Indigenous Manufacturer of Automatic Weather Stations

We, at Ingen Technologies, take great pride in offering indigenously-manufactured Automatic Weather Stations customized for your specific requirements.

End-to-end Management of AWS

- ❖ Manufacturing | Supply | Installation | Operation
- ❖ Capacity of manufacturing 500 AWS per month
- ❖ Customized design with state-of-the-art technology
- ❖ Continuous hardware updation

2. Global Standard Technology

Our sensors conform to the WMO (World Meteorological Organization) standards and are IMD (India Meteorological Department) certified.

- ❖ IMD Certifications: Humidity Sensor, Temperature Sensor, Tipping Bucket Rain Gauge, Silicon Pyranometer and Ultrasonic Wind Sensor

3. Top-notch Team

We leverage our strong in-house team of meteorologists, remote sensing experts, and IoT specialists to provide accurate & real-time weather data & forecast services.

- ❖ In-house R&D, Hardware, & Software teams linked with IIT Kanpur, ST Microelectronics, etc.

4. Support & Services

Our trained technicians are stationed in most of the Indian states to attend to your requirements at shortest possible time.

- ❖ Preventive Maintenance: Every 3 months
- ❖ Sensor Calibration: Twice a year
- ❖ Prioritized Location Visits: As and when scheduled
- ❖ Component Replacement: After a specified period of life
- ❖ Error Resolution: Within 72 hours of reporting

5. Focus on Data Quality

- ❖ Data is being monitored round-the-clock
- ❖ Advanced algorithms & integrity checks are applied on the data
- ❖ Statistical analysis tools capture parameter drifts
- ❖ Automated alerts are generated in-case of data failure

6. Data Quality Checks

- ❖ Syntactic Checks: To ensure that data is as per the sensor resolution and range
- ❖ Climate-range Checks: To ensure that Datum is consistent with month-wise climatology
- ❖ Time-series Consistency: Plausible difference between two successive values based on meteorological heuristics
- ❖ Spatial Consistency: Plausible difference between two nearby stations based on variations
- ❖ Device Consistency: Comparison with nearest IMD and state government weather stations to avoid systematic errors



Ingen's Automated Weather Stations provide continuous automatic observations for weather parameters like air temperature, relative humidity, dew point, precipitation, sunlight intensity, short and longwave solar radiation, wind speed & direction, barometric pressure, soil moisture, soil temperature etc. These parameters remain crucial for accurate weather monitoring.

The AWS mast is available in variable shapes & sizes

- ❖ From 2 m to 10 m unipole, tripod or triangular tower made up of galvanized iron or stainless steel to which various sensors can be attached.
- ❖ The support fixtures and frames for sensors & accessories can also be made as per client's requirements.

AWS Data Flow Diagram





AWS Applications

Weather Forecasting & Weather Data Services




Figure 2

Sensor Management System




Figure 3

Risk Management



Figure 4

Agri Advisory




Figure 5

Technical Specifications of AWS Sensors

Air Temperature

Type : Band gap
 Item # : iTMS101
 Range : -40 to +125°C
 Resolution : 0.1°C
 Accuracy : 0.1°C

Relative Humidity

Type : Solid state /
 Capacitive
 Item # : iHMS101
 Range : 0 to 100%
 Resolution : 0.1% RH
 Accuracy : ±1% RH



Precipitation

Type : TBRG
 Material : ABS
 Item # : iRMS101
 Range : 0.2-900 mm/hr
 Resolution : 0.5mm or better
 Accuracy : ±2%

Barometric Pressure

Type : Solid state
 Item # : iBMS101
 Range : 300-1260 hPa
 Resolution : 0.1 hPa
 Accuracy : ±0.2 hPa
 Output : Digital



Wind Speed

Type : Ultrasonic
 Item # : iWMS2011
 Range : 0 to 80m/sec
 Resolution : 0.1 m/s
 Accuracy : ±2%

Wind Direction

Type : Ultrasonic
 Item # : iWMS2011
 Range : 0 to 359 Deg
 Resolution : 1deg
 Response Time : 1 Sec
 Accuracy : ± 3°



Pyranometer 1

Type : Photodiode
 Item # : iSRMS201
 Range : 0-1800 Wt/m2
 Resolution : 1 Wt/m2

Pyranometer 2

Type : Thermopile
 Item # : iSRMS202
 Range : 0-2000 Wt/m2
 Resolution : 1 Wt/m2

Spectral Range : 400-1100nm
 Accuracy : ± 3%

Spectral Range : 300-2800nm
 Accuracy : ± 3%




PAR Sensor

Type : Photodiode
 Item # : iPARS201
 Range : 0-4000
 μmol/m2/s
 Resolution : 0.1 μmol/m2/s
 Spectral Range : 300-800nm
 Accuracy : ± 5%

Evaporation Sensor

Type : Float or Pully
 Item # : iEVPS201
 PAN Dia : 1200mm
 Range : 0-100 mm/day
 Resolution : 1mm
 Accuracy : ±2%



Soil Temperature

Type : RTD Class B /
 Thermistor
 Item # : iST101
 Range : 0 to +70°C
 Resolution : 0.1°C
 Accuracy : ± 0.2°C

Soil Moisture

Type : FDR
 Item # : iSM101
 Range : 0 to 100% VWC
 Resolution : 0.1 VWC
 Accuracy : ± 3%





Integrated Data logger

Features

- ❖ Ultra “low” power ARM controller
- ❖ 16x2 alphanumeric LCD
- ❖ Watchdog timer available
- ❖ System Reset option available
- ❖ SMS configurable setting command
- ❖ 2G/3G/4G compatible GPRS modem
- ❖ Firmware Over the Air (FOTA) update feature
- ❖ 12 digital/analog channels, 16-bit A/D converter
- ❖ Dedicated 32 kHz oscillator for RTC with calibration
- ❖ Sample intervals configurable from 1 sec to 24 hours
- ❖ Sensor Interface: ADC, SDI-12, SPIs, I2Cs, USARTs, RS232, RS485 etc.
- ❖ System Clock Stability 1 ppm per year, real time clock synchronized with GPS

Specification

Memory: 1GB, extendable upto 64GB

External Power: 12V to 24V DC (48 V maximum)

Power Consumption: < 50mA

Basic Communication Interface: RS232, RS485

Main Power option: Solar panel or 12v DC adapter

Operating Temperature: -40 °C to +60 °C

Operating Humidity range: 0% to 100%



Figure 6

Communication Unit

IDCU for AWS iDAS101

Weather Station sends the summarized weather data at programmable interval of 1 minute to several hours. The messages are sent automatically via GPRS to the central server. In the extreme case of no mobile signal, data is stored in the internal flash memory sufficient to store minimum 12-month of weather data. IDCU also has an option of external memory expandable up to 64GB.

Data transmission through GPRS

- ❖ The IDCU is able to send the weather station data in a compressed format to the central server using HTTPS/FTP/API or other protocol.
- ❖ The data transmission interval is configurable over the air and any new transmissions happen as per the newly configured interval.
- ❖ During a signal loss condition, the IDCU will keep trying for the transmission and resume the transmission once the GPRS network is available.

Power Supply

The weather station is a standalone wireless unit powered by Solar Panel (10W to 75 Wt) charged battery of 3.7V, 20AH. Li-cell battery is preferred to ensure consistent power supply. AWS sensors can work for 30-35 days in extremely rainy weather with fully charged batteries.

POWER REQUIREMENTS

- ❖ Battery 20Ah/3.7V
- ❖ Power consumption <100mA/3.7V
- ❖ Battery can be charged through 230V AC (with suitable adaptor) or a 10W-75 W solar panel

PHYSICAL SPECIFICATIONS

- ❖ Materials: Stainless steel, Plastic, Anodized Aluminum, Iron
- ❖ Height: 1.5 m to 10 m depending on requirement
- ❖ Enclosure: 2* 2 sq m to 5*5 sq m
- ❖ Weight : approx 7 kg - 20 Kg

Application Software

Portal Software

Portal Software aggregates, manages, analyzes, organizes and distributes weather information into a single system tailored to the preferences of different user groups (farmers, agri officers, insurance companies, administrator, etc).

It broadly does the following

- ❖ Data acquisition (from IDCU)
- ❖ Data management & display (real-time, history and forecast)
- ❖ Administrator (manage the web content based on the authorization model)
- ❖ Support section (statistics, SMS, email alerts, data export, etc)
- ❖ Resources - high speed networking, high performance computing and large data storage



Clientele



बिहार सरकार



सत्यमेव जयते

Government of Rajasthan



सत्यमेव जयते



सत्यमेव जयते



সত্যমেব জয়তে



सत्यमेव जयते



MAHYCO



PEPSICO



Bloomberg



Smart Solutions for Secure Tomorrow

INGEN Technologies Private Limited
Corporate office

Plot No 1, Sukhdham Residency, At Village Singhpur
Kacchar Distt. Kanpur - 208017

Contact: +91 6388 903237 | Email: info@theingen.com